



FORMIKO
HYDRAULICS

ROTATOR **FHR 3.000RF**



30
kN

15
kN

900
nm

24
kg

20
l/min



60 \varnothing 25
mm



3/8"
BSP



250
bar



3/8"
BSP



200
bar



300
bar

Hydraulic rotator FHR 3.000RF is cost-effective solution generally for seasonal use in forestry, agriculture, road and building construction, general cargo and material handling.

Rotator's upper mount is applied in EYE form factor of the knuckle joint. Robust and tough built to withstand even overloads. The wide of eye is common standard width 60mm and the knuckle pin diameter 25mm.



FHL 01-A/B-
60/25






FHL 01B-
A/B-60/25

Rotator lower mount is applied in FLANGE form factor to mount direct on grapple / tool surface by fixing with screws

173
17(x4)
mm

GO/GC
3/8"
BSP



For additional information relating to price levels and technical data, please contact sales@formiko.lv

Formiko Hydraulic s Ltd

Dzirclima Str. 119 k-1,
Rīga LV1055 LATVIA

+371 294 49 552

+371 264 59 383

sales@formiko.lv

www.formiko.lv

On request by special conditions there are metric nipples available for rotator FHR 3.000RF



FORESTRY



GENERAL CARGO



AGRICULTURE



CONSTRUCTION



Current document is automatic generated at www.formiko.lv on 01/04/2018.
Please always make sure that it's up to date and try to be paperless!



Hydraulic rotator FHR 3.000RF is cost-effective solution generally for seasonal use in forestry, agriculture, road and building construction, general cargo and material handling.



Rotator's upper mount is applied in EYE form factor of the knuckle joint. Robust and tough built to withstand even overloads. The wide of eye is common standard width 60mm and the knuckle pin diameter 25mm.



Rotator lower mount is applied in FLANGE form factor to mount direct on grapple / tool surface by fixing with screws



Rotator FHR 3.000RF based on reliable vane type hydraulic motor which delivers torque up to 900Nm at 25MPa.



Formiko rotator FHR 3.000RF is compatible with FHL 01-A/B-60/25 and FHL 01B-A/B-60/25 series links.



Rotator for shipping is packed in compact solid cardboard box with dimensions 340x230x240mm.



We providing TWO year warranty for this rotator.

For additional information relating to price levels and technical data, please contact sales@formiko.lv

Formiko Hydraulic s Ltd

Dzirclima Str. 119 k-1,
Riga LV1055 LATVIA

+371 294 49 552

+371 264 59 383

sales@formiko.lv

www.formiko.lv

On request by special conditions there are metric nipples
available for rotator FHR 3.000RF



FORESTRY



GENERAL CARGO



AGRICULTURE



CONSTRUCTION

